



## A.R.G.O. (Auto Regulating Gas Operating)

Two symmetrical gas ports placed under the barrel close to the combustion chamber. Both ports have a short stroke piston set back to discharge the hot gases at high pressure, in 100% safe and constant cycle, free from clogging by residuals.

#### **4 GHOST RING SIGHT OPTIC FIBRE**

The M4 is equipped as standard with a Ghost Ring Sight that is adjustable in windage and elevation and protected by side lugs in heat-treated steel. (Optic fibre dots, 1 red in front and 2 green in rear).

#### 2 MULTI RAIL SYSTEM

The weapon's MIL-STD-1913 top Picatinny Rail means that it is possible to fit all types of targeting device (from optical sights to red dot sights, light intensifiers etc.). The new forearm with multi rail system allows the mount of mini-rails (5-slots) all over at 3/6/9/12 o'clock.

#### **5** MODULAR BARRELS

Modularity for barrels (18,5" or 14") and magazines configuration (different types) with door-breaching device that can be installed on all barrels.

#### **3** STOCK 5 POSITIONS

The M4 is also available with telescopic stock that can be adjusted in 5 positions. Easily removable to changing in Pistol Grip or standard stock.

### 6 BIGGER BOLT HANDLE AND BOLT RELEASE BOTTOM

Bigger Bolt Handle and Bolt Release Button for easy handling.





# BENELLI DEFENSE











െ	
0	
4	
7	
0	
0	
മ	
O	

M4 TECHNICAL SHEET	M4 BLACK 18,5" TELESCOPIC STOCK	M4 BATTLE BROWN 14" TELESCOPIC STOCK
<b>OPERATION</b> Semiautomatic Auto Regulating Gas Operating	•	• =
GAUGE	12	12
CHAMBER	3" MAGNUM	3" MAGNUM
SAFETY Mechanic on trigger and automatic on disconnector	•	•
CUT-OFF for rapid cartridge replacement and red cocked hammer indicator	•	
<b>TRIGGER LOAD</b> 2.500-3.250Kg / 30-36 N	•	•
BARREL LENGTH (mm)	470	355
MAGAZINE CAPACITY 6 Magnum or 7 standard cartridges (+1 in chamber)	•	

	M4 BLACK 18,5" TELESCOPIC STOCK	M4 BATTLE BROWN 14" TELESCOPIC STOCK
MAGAZINE CAPACITY 4 Magnum or 5 standard cartridges (+1 in chamber)		•
STOCK DISTANCE FROM TRIGGER (mm)	355	355
SIGHTS  Ghost Ring Sights in Optic Fibre  (Adjustable Rear/Fixed Front)  Picatinny Rail		•
STOCK in tecnopolymer telescopic stock, collapsible to 118 mm	•	•
<b>WEIGHT</b> g (unloaded weapon)	3900	3670
TOTAL LENGTH (mm)	1005 extended 887 retracted	892 extended 774 retracted
FINISH Black anodized receiver, hammered barrel Ni-Cr-Mo (inner Chrome lining/exterior phosphate coating)	•	48
EXTERNAL CERAMIC COATING (federal standard field grab) that confers the treated surfaces of the M4 exceptional resistance against extreme environmental conditions, erosion, corrosion and scratching		

M4 is also available with 14" barrel and M4 BATTLE BROWN with 18,5" barrel



QUALITY ASSURANCE SYSTEM CERTIFIED BY THE ITALIAN MINISTRY OF DEFENCE, GENERAL DEPARTMENT OF LAND WEAPONS, ACCORDING TO LAW.

Benelli Armi S.p.A. Via della Stazione, 50 61029 Urbino (PU) - Italy ph. +39 0722 3071 fax +39 0722 307206

