



1 DUAL MODE

Lever to switch from semiautomatic to pump action for lethal and less lethal applications.

4 MODULAR BARRELS

Modularity for barrels (18,5" or 14,5") and magazines configuration (different types) with door-breaching device that can be installed on all barrels

2 QUICK DETACHMENT STOCK SYSTEM

BMS, "Benelli Modular Stock" System: from Telescopic 5-pos. into Grip Handle No-Stock in seconds. Other options: Pistol Grip & Standard Stock.

5 GHOST RING SIGHT OPTIC FIBRE

Optic Fibre Ghost Ring Sights (1 Red Front Dot /2 Green Rear Dots) Adjustable in windage and elevation and protected by side lugs in heat-treated steel.

3 QUICK DETACHMENT SLING SWIVEL SYSTEM

Quick detachable sling swivel systems (on both sides front, rear and on grip)

6 PICATINNY RAIL

Forearm with picatinny Rail to mount flashlights, lasers etc. and picatinny rail on top

7 BIGGER BOLT HANDLE & BOLT RELEASE BUTTON

Bigger Bolt Handle and Bolt Release Button for easy handling.





BENELLI DEFENSE













	M3 18,5" TELESCOPIC STOCK	M3 14,5" TELESCOPIC STOCK	M3 14,5" + DOOR-BREACHER GRIP HANDLE
OPERATION Benelli Inertial System semiautomatic convertible to Pump Action	•	•	•
GAUGE	12	12	12
CHAMBER	3" MAGNUM	3" MAGNUM	3" MAGNUM
SAFETY Mechanic on trigger and automatic on disconnector	•	•	•
CUT-OFF for rapid cartridge replacement and red cocked hammer indicator	•	•	•
TRIGGER LOAD 2.500-3.250 Kg / 22-28 N	•	•	•
BARREL LENGTH (mm)	470	355	355
MAGAZINE CAPACITY 6 Magnum or 7 standard cartridges (+1 in chamber)	•		
MAGAZINE CAPACITY 3 Magnum or 4 standard cartridges (+1 in chamber)		•	•

	M3 18,5" TELESCOPIC STOCK	M3 14,5" TELESCOPIC STOCK	M3 14,5" + DOOR-BREACHER GRIP HANDLE
STOCK DISTANCE FROM TRIGGER (mm)	355 extended 237 retracted	355 extended 237 retracted	
SIGHTS Ghost Ring Sights in Optic Fibre (Adjustable Rear/Fixed Front) Picatinny Rail	•		
Quick detach stock system	•	•	
STOCK in technopolymer telescopic stock, collapsible to 118 mm	•		
WEIGHT g (unloaded weapon)	3550	3430	2805
TOTAL LENGTH (mm)	1006 extended 888 retracted	910 extended 792 retracted	650
FINISH Black anodized receiver, hammered barrel Ni-Cr-Mo (inner Chrome lining/exterior blued coating)	•	•	



QUALITY ASSURANCE SYSTEM CERTIFIED BY THE ITALIAN MINISTRY OF DEFENCE, GENERAL DEPARTMENT OF LAND WEAPONS, ACCORDING TO LAW.

Benelli Armi S.p.A. Via della Stazione, 50 61029 Urbino (PU) - Italy ph. +39 0722 3071 fax +39 0722 307206

